

## FIRE PROTECTION OUT OF SERVICE

Attach this portion of the permit tag to the closed valve

### DO NOT REMOVE TAG UNTIL VALVE IS REOPENED

Protecting:	Valve n	10:	
Impaired:	/ / DATE		a.m./p.m.
	DATE	TIME	
Ву:			
Authorised by (F	ire Safety Manager):		
Reason for closi	ng:		
Restored:	/ / DATE		a.m./p.m.
By:			
Verified by (Fire	Safety Manager):		
LIDON CC	MDI ETION D	ETI IDN TI	JIC TAC
	OMPLETION R IE FIRE SAFE		
IOIF			
10 11			
		oermit tad	to be
This po	ortion of the p	permit tag Safety Ma	to be
This po		oermit tag Safety Ma	to be inager
This po	ortion of the p	oermit tag Safety Ma	to be anager
This portained	ortion of the post the post the Fire state of the Protection	Safety Ma	anager
This portent of the second of	ertion of the period by the Fire services	Safety Ma	anager
This por retained	ortion of the post the post the Fire state of the Protection	Safety Ma	anager
This portained  IMPAIRED FIRE  Protecting:  Impaired:	PROTECTION  Valve no date	Safety Ma	anager
This portained  IMPAIRED FIRE  Protecting:  Impaired:  By:	ertion of the period by the Fire services	Safety Ma	anagera.m./p.m.
This portained  IMPAIRED FIRE  Protecting:  Impaired:  By:  Authorised by (F	PROTECTION  Valve r  DATE  Varier Safety Manager):	Safety Ma	anager a.m./p.m.
This portained  IMPAIRED FIRE  Protecting:  Impaired:  By:  Authorised by (F	PROTECTION  Valve r  DATE	Safety Ma	anager a.m./p.m.
This portained  IMPAIRED FIRE  Protecting:  Impaired:  By:  Authorised by (F	PROTECTION  Valve r  DATE  Varier Safety Manager):	Safety Ma	anager a.m./p.m.
This portained  IMPAIRED FIRE  Protecting:  Impaired:  By:  Authorised by (F	PROTECTION  Valve r  DATE  Varier Safety Manager):	Safety Ma	anager a.m./p.m.
This portes of the control of the co	PROTECTION  Valve n  DATE  DATE	Safety Ma	anagera.m./p.m.
This portes of the control of the co	PROTECTION  Valve r  DATE  Varier Safety Manager):	Safety Ma	anagera.m./p.m.
This portes are tained.  IMPAIRED FIRE Protecting: Impaired:  By: Authorised by (F Reason for closi  To be restored:	PROTECTION  PROTECTION  Valve n  DATE  PATE  PATE  PATE  PATE	TIME	anagera.m./p.ma.m./p.m.
This portes are taken of the protecting:	PROTECTION  Valve n  DATE  DATE	TIME	anagera.m./p.ma.m./p.m.



# FIRE PROTECTION OUT OF SERVICE

## Attach this portion of the permit tag to the closed valve

Before authorising valve closure, the Fire Safety Manager should evaluate the work to be done and confirm that precautions have been taken to prevent fires and to reduce the downtime of the sprinkler system.

#### Before impairment

Ensure all necessary materials are available for repairs/alterations before any valve closure or system impairment (planned impairments).

Alert appropriate personnel and the emergency response team, so safeguards can be taken. Appoint someone to reopen valves or enable systems in the event of a fire if safe to do so

Notify fire and emergency services of fire protection system impairments

Notify your insurance broker.

Discontinue hazardous operations (e.g. hot work, welding and cutting operations; handling of flammable liquids).

Obtain extra fire extinguishers, hoses and other manual fire-fighting equipment.

Establish a continuous fire watch for the area(s) affected by the impaired protection systems.

Fasten this tag (top portion of permit) to the impaired system.

Record valve closures on the Record of valve closures document

The information in this document is presented by Liberty Specialty Markets (Liberty), a trading name of Liberty Mutual Insurance Company (ABN 61 086 083 605) incorporated in Massachusetts, USA (the liability of members is limited); Liberty Specialty Markets (Liberty), a trading name of Liberty Specialty Markets Limited (No. 2400200), incorporated in Hong Kong; Liberty Specialty Markets Pte Limited (Registration No. 1: F12093) trading as Liberty Specialty Markets, Labuan Branch; and Liberty Specialty Markets Pte Limited (UEN 201538069C), incorporated in Singapore. It is acknowledged that this document is not intended to identify all hazards that may exist, nor is it intended to be an exhaustive review of all possible eventualities. The recommendations contained in this document are purely advisory and the decision and responsibility for implementation rests with the sites management. This document is intended to provide general information only. You should not act on the basis of information contained within this document without first obtaining specific professional advice. Liberty makes on representation or warranty in relation to the accuracy or completeness of factual information contained in this document. Liability for indirect or consequential loss arising out of or in connection with this document is expressly excluded. This information is current as at September 2017.

### During the repair work

- Complete the work while the premises are fully attended where possible.
- Complete the work while the premises are fully attended where possible
   Monitor the progress of the work and maintain the fire watch throughout.
- Display the lower portion of this permit on a fire protection status board for the duration of the impairment.

### After completion of work

Immediately restore fire protection systems to service.

Open and lock wide open sprinkler systems and water supply control valves and do main drain tests downstream from water-based extinguishing systems.

If tests are satisfactory, relock the valves open.

Detach this tag when you have verified that this system is operational.

Fasten a yellow DO NOT SHUT VALVE tag to the reopened valve.

Secure fire protection control/alarm panels and verify alarms, fire protection

systems and water-based extinguishers are operational.

Ensure all red tags are accounted for, match each with the lower portion of its permit, and complete and sign both portions.

Return any system control keys to the usual place.

Update the Record of valve closures document to reflect the reopening of

Notify appropriate personnel, fire and emergency services, the alarm company and broker of the fire protection restoration.

The lower portion of the permit tag should be detached and the front displayed on a fire protection status board or other prominent place to act as a reminder to the Fire Safety Manager of the fire protection impairment. It should remain on display until the fire protection has been restored and the upper portion of the permit tag returned. Both parts should then be completed and retained as a permanent record.

parts should then be completed and retained as a permanent record.

The information in this document is presented by Liberty Specialty Markets (Liberty), a trading name of Liberty Mutual Insurance Company (ABN 61 086 083 605) incorporated in Massachusetts, USA (the liability of members is limited); Liberty Specialty Markets (Liberty), a trading name of Liberty Specialty Markets Limited (No. 2400200), incorporated in Hong Kong; Liberty Specialty Markets Pte Limited (Registration No. L. F12903) trading as Liberty Specialty Markets Pte Limited (USA 201538069C), incorporated in Singapore. It is acknowledged that this document is not intended to identify all hazards that may exist, nor is it intended to be an exhaustive review of all possible eventualities. The recommendations contained in this document are purely advisory and the decision and responsibility for implementation rests with the sites anaagement. This document is intended to provide general information only. You should not act on the basis of information contained within this document without first obtaining specific professional advice. Liberty makes no representation or warranty in relation to the accuracy or completeness of factual information contained in this document. Liability for indirect or consequential loss arising out of or in connection with this document is expressly excluded. This information is current as at September 2017.